

Model 58XRB

Hi-Performance Multi-Purpose Lift



**TOTAL HYDRAULIC
JOYSTICK BASKET CONTROLS
PROPORTIONAL BASE CONTROLS
5000# LIFT WINCH
400# JIB WINCH
ROTATING BASKET
POWER LEVELED BASKET**



Standard Features:

Power Leveling and Rotating 2 man aluminum 24" X 60" basket
All functions pressure relieved for a balanced system
Joystick proportional controls in basket
Hydraulic powered self-leveling basket
Remote engine throttle, and engine start and stop from the base and basket
Tandem Hydraulic cylinders for extension (no cables)
All hydraulic for smooth three function control at the same time
Rotation motor direct coupled to gearbox
PTO powered hydraulic pump with electric shift on.
All operations can run at the same time
Power retract by tandem hydraulic cylinders
360 degree working radius
Heavy Duty lift capacity
All Hydraulic powered extension and retraction
Quick connect load line to convert from service to crane lifting
Rotation drive with adjustment collar for exacting mesh to bull gear
Single stage elevation cylinder, double acting
5000 lb. rated load line

Options:

110 Volt in basket
Welding leads in basket
Auxiliary hydraulic jib winch in the basket 400 Lbs. rated
Air or power washer leads in basket

Minimum Truck Specifications:

10,000 Lb. Front Axle, 17,000 Rear Axle
25,950 G.V.W.:120" CA: 194"WB
Truck Frame - 2,000,000 RBM
Front and Rear outrigger stabilizers required

NON INSULATED - ELECTROCUTION HAZARD

STATE & FEDERAL REGULATIONS REQUIRE CERTAIN CLEARANCES OF ELECTRICAL POWER LINES.