



Technical Data PB74 - 48

Operation mode:

In/outdoor use

Performance: Work height Platform height Drivable at full height Platform height, stowed Platform capacity Platform size Maximum platform size

Dimensions: Width Length Maximum turn angle Turning radius outside Height, lowered Transport height

Weight: Gross weight Electric motor Battery capacity Gradability/slope performance **Differential lock**

Leveling system: Leveling stroke Height compensation Maximum bearing load

15.7 in 7.8 in 32KN / 7194 pound force

www.reachmaster.com

Standard equipment:

- Dual maintenance free scissor system
- Corrosion protected power coated paint •
- Weight sensor/control for platform and scissor system
- Dual controls (control box plus ground controls) •
- PBdigiConnect ® telemetric diagnostic system
- Work height limitation

ReachMaster, Inc. 1416 D Stonehollow Dr. Kingwood, TX 77339

74 ft 67 ft Yes 8 ft 4 in 991 lbs 157 in x 47 in 215 in x 47 in

48 in (4 ft) 177 in (14 ft 8 in) 90° 159 in (13 ft 2 in) 145.3 in (12 ft 1 in) 113" in (9 ft 4 in)

22,686 lbs 16kW 48 v 560 Ah Aquamatik 25° Standard



The information and data is not considered binding without express confirmation by ReachMaster, Inc. and subject to change without notice

Phone	281-358-7088
Toll Free	866-358-7088
Fax	281-359-3500



